

convoChill (cC) D4

Blast chiller-freezers

Optimal result for soft & hard chilling and shock-freezing

Dial & Touch control

- ✓ Standard
- Does not apply
- Optional



	5.10 UC	5.10	10.10	15.10	15.20	10.10	15.10	15.20	20.10	
Specifications	Dimensions width x depth x height	730 x 660 842	840 x 770 x 930 mm	840 x 831 x 1548 mm	840 x 930 x 2002 mm	840 x 1300 x 2002 mm	840 x 990 x 1548 mm	840 x 1090 x 2002 mm	840 x 1460 x 2002 mm	890 x 1371 x 2410 mm
	Electrical connected load rating 230VAC 50/60Hz 1/N/PE	1264 W	1350 W	-	-	-	-	-	-	-
	Electrical connected load rating 400VAC 50/60Hz 3/N/PE	-	-	3250 W	4000 W	4050 W	5440 W	7800 W	7800 W	3900 W
	Capacity cooling 90 min +90 °C / +3 °C	14 kg	20 kg	35 kg	65 kg	70 kg	35 kg	65 kg	70 kg	80 kg
	Capacity freezing 240 min +90 °C / -18 °C	10 kg	12 kg	25 kg	50 kg	55 kg	25 kg	50 kg	55 kg	65 kg
	Capacity GN 1/1	5	5	10	15	30	10	15	30	-
	Capacity GN 2/1	-	-	-	-	15	-	-	15	-
	Capacity EN 600 x 400 mm	-	5	10	15	30	10	15	30	-
	Capacity EN 600 x 800 mm	-	-	-	-	15	-	-	15	-
	Pitch GN / EN	68 mm	68 mm	68 mm	68 mm	68 mm	68 mm	68 mm	68 mm	68 mm
Capacity trolley GN 1/1, EN 600 x 400 mm	-	-	-	-	-	-	-	-	20	
Version	Devapo cookbook with 99 preprogrammed recipes	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Low temperature cooking and regeneration function	-	-	-	-	-	✓	✓	✓	-
	Automatic alarm signaling when opening the chiller door	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Automatic defrost	-	✓	✓	✓	✓	✓	✓	✓	✓
	Digital setting of time and temperature or core temperature	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Touch control for visual function description and extensive options	-	-	-	-	-	✓	✓	✓	-
	HACCP - data storage	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Core temperature probe incl. commissioning function check/self-diagnosis check	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Ice - shock freeze function	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Height-adjustable legs	-	✓	✓	✓	✓	✓	✓	✓	-
	Emergency - Mode: employability to storage cooling	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Right-hinged closed stainless steel door	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Startup function check commissioning / self diagnosis	✓	✓	✓	✓	✓	✓	✓	✓	✓
	All stainless steel	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Evaporator and condenser coated as standard against corrosion	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Ambient outside temperature due to special thermal insulation	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Removable condenser filter	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Removable ventilation plate	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Seamless bottom and rounded corners in the chill chamber	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Advanced / robust fan made of corrosion-resistant material	✓	✓	✓	✓	✓	✓	✓	✓	✓
Service-friendly electrical compartment	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Removable suspension guides	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Connection cable 230VAC with plug included 3 x 1,5 mm ²	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Connection cable 400VAC 5 x 1,5 mm ²	-	-	✓	✓	✓	✓	✓	✓	✓	
Optional	Special connection voltages	○	○	○	○	○	○	○	○	○
	ConvoControl automatic HACCP - management system - RS485	○	○	○	○	○	○	○	○	○
	Interface RS485	○	○	○	○	○	○	○	○	○
	Low legs i.c.m. special drip tray / drip tray	-	○	○	○	○	○	○	○	○
	Left hinged door	○	○	○	○	○	○	○	○	○
	Ozone generator / UV lamp sterilizer	-	○	○	○	○	○	○	○	○
	Stainless steel swiveling wheels can be swiveled	-	○	○	○	○	○	○	○	○
	USB data logger	-	○	○	○	○	○	○	○	○
	Ramp	-	-	-	-	-	-	-	-	-
	Water cooled condenser	○	○	○	○	○	○	○	○	○
Add.	Trolley 20 x GN 1/1	-	-	-	-	-	-	-	○	
	Grid EN 600 x 400 mm	-	○	○	○	○	○	○	○	

(!) Other features are available on request. Ask your product specialist.