

# careconceptLine (ccL)

## Built-in combi-steamers

Optimal result at regeneration and all preparations

Premium (P) control

- ✓ Standard
- Does not apply
- Optional



	6.06	6.10	10.10		
<b>Specifications</b>	Dimensions width x depth x height	595 x 600 x 885 mm	595 x 800 x 885 mm	595 x 800 x 1110 mm	
	Electrical connected load rating 230VAC 50/60Hz 1/N/PE	3,0 kW	3,6 kW	-	
	Electrical connected load rating 400VAC 50/60Hz 3/N/PE	5,7 kW	7,1 kW	10,5 kW	
	Capacity in number of persons	6-10	10-16	16-24	
	Capacity GN 2/3	6 (40) / 4 (65)	-	-	
	Capacity GN 1/1	-	6 (40) / 4 (65)	10 (40) / 6 (65)	
	Capacity plates Ø 280 mm	4	8	12	
Pitch GN	40 / 65 mm	40 / 65 mm	40 / 65 mm		
<b>Version</b>	Advanced Closed System	✓	✓	✓	<b>unique</b>
	Cookbook with preprogrammed recipes	✓	✓	✓	
	Multiple dehumidification	✓	✓	✓	
	Unlimited programs	✓	✓	✓	
	Fully automatic cleaning system, 5 choice of steps	✓	✓	✓	<b>unique</b>
	Tray Timer time controlled loading and unloading chamber	✓	✓	✓	
	Timecontrolled starting time	✓	✓	✓	
	Self-diagnostic system for error detection and description	✓	✓	✓	
	Halogen lighting with shockproof glass window	✓	✓	✓	
	Hygienic door closure and seamless rounded corners in oven chamber	✓	✓	✓	
	Removable multifunctional slides and high-tech ventilation plate	✓	✓	✓	
	Fully stainless steel	✓	✓	✓	
	Door Lock System - basic	✓	✓	✓	
	Right or left hinged door option	✓	✓	✓	<b>choice</b>
	Antibacterial lock with demistingmode, safety and functional features	✓	✓	✓	
Steam accumulator	✓	✓	✓		
Double glass door with integrated end stop	✓	✓	✓		
Built-in system certified incl. Roll-in/Roll-out service system, integrated condensing hood with filter, stainless steel front finishing	✓	✓	✓	<b>unique</b>	
Core temperature probe multi-point measurement	✓	✓	✓		
<b>Optional</b>	Slide frame with extendable slide system	○	○	○	<b>new</b>
	Connection cable 230VAC with plug 2,5 m 3 x 2,5 mm <sup>2</sup>	○	○	-	
	Connection cable 400VAC 5 x 2,5 mm <sup>2</sup>	○	○	○	
	Side extraction at door opening	○	○	○	
	Black edition	○	○	○	<b>new</b>
	Black edition for stand-alone version	○	○	○	
Condensation hood for stand-alone version	○	○	○		
<b>Additional</b>	Double water installation kit for connection between water supply and water filter system	○	○	○	
	Pantry / mobile pantry / personalized pantry	○	○	○	
	GN starter kit set 1 consists of grids, basket and baking tray	○	○	○	
	Devapo water filter system for descaling prior to machine water inlet (only in combination with water supply and drain)	○	○	○	
	Water connection kit	○	○	○	
HACCP - viewer for evaluating the HACCP - documentation, incl. USB - stick	○	○	○		

(!) Other features are available on request. Ask your product specialist.



# careconceptLine (ccL)

## Built-in combi-steamers

Optimal result at regeneration and all preparations

Premium Advanced (PA) control

- ✓ Standard
- Does not apply
- Optional



	6.06	6.10	10.10		
<b>Specifications</b>	Dimensions width x depth x height	595 x 600 x 885 mm	595 x 800 x 885 mm	595 x 800 x 1110 mm	
	Electrical connected load rating 230VAC 50/60Hz 1/N/PE	3,0 kW	3,6 kW	-	
	Electrical connected load rating 400VAC 50/60Hz 3/N/PE	5,7 kW	7,1 kW	10,5 kW	
	Capacity in number of persons	6-10	10-16	16-24	
	Capacity GN 2/3	6 (40) / 4 (65)	-	-	
	Capacity GN 1/1	-	6 (40) / 4 (65)	10 (40) / 6 (65)	
	Capacity plates Ø 280 mm Pitch GN	4 40 / 65 mm	8 40 / 65 mm	12 40 / 65 mm	
<b>Version</b>	Advanced Closed System	✓	✓	✓	<b>unique</b>
	Cookbook with preprogrammed recipes	✓	✓	✓	
	Multiple dehumidification	✓	✓	✓	
	Unlimited programs	✓	✓	✓	
	Fully automatic cleaning system, 5 choice of steps	✓	✓	✓	<b>unique</b>
	Tray Timer time controlled loading and unloading chamber	✓	✓	✓	
	Timecontrolled starting time	✓	✓	✓	
	Self-diagnostic system for error detection and description	✓	✓	✓	
	Halogen lighting with shockproof glass window	✓	✓	✓	
	Hygienic door seal and seamless rounded corners in oven chamber	✓	✓	✓	
	Removable multifunctional slides and high-tech ventilation plate	✓	✓	✓	
	Fully stainless steel	✓	✓	✓	
	Door Lock System - basic	✓	✓	✓	
	Right or left hinged door option	✓	✓	✓	<b>choice</b>
	Antibacterial lock with demistingmode, safety and functional features	✓	✓	✓	
	Steam accumulator	✓	✓	✓	
Double glass door with integrated end stop	✓	✓	✓		
Built-in system certified incl. Roll-in/Roll-out service system, integrated condensing hood with filter, stainless steel front finishing	✓	✓	✓	<b>unique</b>	
Core temperature probe multi-point measurement	✓	✓	✓		
HACCP - data storage	✓	✓	✓		
Touch screen with intuitive, self-explanatory usage user interface, activated in icons and pictures	✓	✓	✓		
<b>Optional</b>	Automatic Door Lock System - safe	○	○	○	<b>unique</b>
	Slide frame with extendable slide system	○	○	○	<b>new</b>
	Connection cable 230VAC with plug 2,5 m 3 x 2,5 mm <sup>2</sup>	○	○	-	
	Connection cable 400VAC 5 x 2,5 mm <sup>2</sup>	○	○	○	
	Side extraction at door opening	○	○	○	
	Black edition	○	○	○	<b>new</b>
	Black edition for stand-alone version	○	○	○	
Condensation hood for stand-alone version	○	○	○		
Condensation hood for 2in1 stand-alone version	○	○	○		
<b>Additional</b>	Double water installation kit for connection between water supply and water filter system	○	○	○	
	Pantry / mobile pantry / personalized pantry	○	○	○	
	GN starter kit set 1 consists of grids, basket and baking tray	○	○	○	
	Devapo water filter system for descaling prior to machine water inlet (only in combination with water supply and drain)	○	○	○	
	Water connection kit	○	○	○	
HACCP - viewer for evaluating the HACCP - documentation, incl. USB - stick	○	○	○		



(!) Other features are available on request. Ask your product specialist.